

AD 2 AERODROMES**ESGJ 2.1 AERODROME LOCATION INDICATOR AND NAME****ESGJ – JÖNKÖPING****ESGJ 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

- | | | |
|----|--|---|
| 1. | ARP coordinates and site at AD | 574530N 0140409E RWY 1200 m from THR 01 |
| 2. | Direction and distance from (city) | WSW 3.5 NM from Jönköping |
| 3. | Elevation/Reference temperature | 742 ft/+21.6°C |
| 4. | Geoid undulation at AD ELEV PSN | 108 ft |
| 5. | MAG VAR/Annual change | 5° E 2020/+0.2 increasing |
| 6. | Administration, address, telephone, fax, AFS | Jönköping Airport AB
Jönköping flygplats
SE-555 93 Jönköping
TEL: +46 (0)36 31 12 00
E-mail: info@jonkopingairport.se
AFS: ESGJZTX
Website: www.jonkopingairport.se |
| 7. | Types of traffic permitted (IFR/VFR) | IFR/VFR. Max RWY ref code 4E |
| 8. | Remarks | PPR outside TWR HR of OPS.
PPR for commercial traffic and aircraft exceeding MTOM 4000 kg.
Requests shall be made during hours of AD administration to:
groundhandling@jonkopingairport.se or TEL: +46 (0)36 31 12 11. |

ESGJ 2.3 OPERATIONAL HOURS

- | | | |
|-----|---|--|
| 1. | AD Administration
AD Operating hours | MON-FRI 0730-1530 (0630-1430)
Ref AIP SUP/NOTAM |
| 2. | Customs and immigration | O/R TEL +46 (0)31 63 38 00 |
| 3. | Health and sanitation | As AD operating hours, Designated quarantine AD |
| 4. | AIS Briefing Office | FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc |
| 5. | ATS Reporting Office (ARO) | As ATS |
| 6. | MET Briefing Office | FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc |
| 7. | ATS | Ref AIP SUP/NOTAM |
| 8. | Fuelling | As AD operating hours |
| 9. | Handling | As AD operating hours |
| 10. | Security | As AD operating hours |
| 11. | De-Icing | As AD operating hours |
| 12. | Remarks | Increased charges outside AD operating hours TEL +46 (0)36 31 12 11. |

ESGJ 2.4 HANDLING SERVICES AND FACILITIES

1.	Cargo-handling facilities	All types available
2.	Fuel/oil types	Fuel Jet A1, 100LL Oil -
3.	Fuelling facilities/discharge capacity	Jet A1: 40,000l fuel truck/150,000l stationary 100LL: 20,000l
4.	De-icing facilities	Type I and II mobile unit
5.	Hangar space for visiting ACFT	O/R: groundhandling@jonkopingsairport.se or TEL: +46 (0)36 31 12 11
6.	Repair facilities for visiting ACFT	Limited
7.	Remarks	For payment of fuel AIR BP, VISA, Mastercard and American Express accepted.

ESGJ 2.5 PASSENGER FACILITIES

1.	Hotels	In Jönköping
2.	Restaurants	At AD
3.	Transportation	Buses, taxi, rental cars
4.	Medical facilities	In Jönköping
5.	Bank and Post Office	In Jönköping
6.	Tourist Office	In Jönköping
7.	Remarks	Conference facilities at AD

ESGJ 2.6 RESCUE AND FIRE FIGHTING SERVICES

1.	AD category for fire fighting	CAT 7, higher O/R TEL +46 (0)36 31 12 33.
2.	Rescue equipment	By arrangement, municipal rescue service
3.	Capability for removal of disabled aircraft	By arrangement
4.	Remarks	-

ESGJ 2.7 SEASONAL AVAILABILITY – CLEARING

1.	Types of clearing equipment	Snowploughs, blowers, sweepers, slingers, spreaders
2.	Clearance priorities	RWY, TWY, Apron
3.	Remarks	RWY 11/29 closed between oct 1 - apr 30

ESGJ 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

1.	Apron surface and strength	Apron ASPH PCN 55 F/B/X/T
2.	Taxiway width, surface and strength	TWY A 23 m ASPH PCN 55 F/B/X/T TWY B 23 m ASPH PCN 55 F/B/X/T
3.	ACL, location and elevation	See ESGJ 2-1
4.	VOR checkpoints	-
5.	INS checkpoints	-
6.	Remarks	TWY B max aircraft ref code 4C

ESGJ 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

- | | | |
|----|---|--|
| 1. | Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of ACFT stands | Taxi guide lines and signs. Marshalling available
See ESGJ 2-1 |
| 2. | RWY and TWY markings and LGT | RWY 01/19: Designator, THR, TDZ, CL and edges are day marked.
RTHL, REDL, RENL.
11/29: White flat rectangular markers, size 1m by 3m, no lights.

TWY A: CL, HLDG day marked. Edge lights, RGL
B: CL, HLDG day marked. Edge lights, RGL |
| 3. | Stop bars | - |
| 4. | Remarks | - |

ESGJ 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT in metres	Markings/ Type, colour	Remarks
a	b	c	d	e	f
ESGJ1	Forest	574616.5N 0140436.0E	228.0 / -	-	-
ESGJ2	Forest	574615.6N 0140442.1E	229.8 / -	-	-
ESGJ3	Forest	574618.7N 0140442.7E	231.1 / -	-	-
ESGJ4	Mast	574622.3N 0140438.0E	232.4 / -	-	-
ESGJ5	Forest	574624.7N 0140449.4E	233.8 / -	-	-
ESGJ6	Forest	574628.8N 0140437.6E	236.5 / -	-	-
ESGJ7	Forest	574629.3N 0140439.1E	237.2 / -	-	-
ESGJ8	Forest	574632.8N 0140437.6E	244.4 / -	-	-
ESGJ9	Forest	574642.7N 0140441.9E	250.0 / -	-	-
ESGJ10	Forest	574642.7N 0140442.2E	250.4 / -	-	-
ESGJ11	Forest	574705.7N 0140450.9E	260.7 / -	-	-
ESGJ12	Forest	574706.5N 0140450.3E	261.8 / -	-	-
ESGJ13	Forest	574706.5N 0140450.8E	262.0 / -	-	-
ESGJ14	Forest	574443.5N 0140344.6E	227.3 / -	-	-
ESGJ15	Antenna	574444.4N 0140335.0E	227.8 / -	-	-
ESGJ16	Forest	574442.2N 0140344.8E	229.0 / -	-	-
ESGJ17	Forest	574434.0N 0140343.3E	235.8 / -	-	-
ESGJ18	Forest	574433.3N 0140340.1E	236.3 / -	-	-
ESGJ19	Forest	574424.2N 0140337.4E	245.1 / -	-	-
ESGJ20	Forest	574410.5N 0140314.5E	251.9 / -	-	-
ESGJ21	Forest	574404.4N 0140322.6E	253.8 / -	-	-
ESGJ22	Forest	574400.2N 0140308.7E	255.6 / -	-	-
ESGJ23	Forest	574351.7N 0140316.2E	260.0 / -	-	-
ESGJ24	Forest	574346.0N 0140317.1E	263.4 / -	-	-
ESGJ25	Forest	574340.5N 0140320.1E	268.9 / -	-	-
ESGJ26	Forest	574340.5N 0140319.8E	269.5 / -	-	-
ESGJ27	Forest	574205.6N 0140119.5E	312.4 / -	-	-
ESGJ28	Forest	574204.5N 0140124.0E	314.0 / -	-	-
ESGJ29	Forest	574201.8N 0140113.9E	316.4 / -	-	-
ESGJ30	Forest	574201.7N 0140113.8E	317.2 / -	-	-

In Area 3					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
Not available					

ESGJ 2.11 METEOROLOGICAL INFORMATION PROVIDED

- | | |
|--|--|
| 1. Associated MET Office | STOCKHOLM/Arlanda |
| 2. Hours of service
MET Office outside hours | H24 |
| 3. Office responsible for TAF preparation
Periods of validity, interval of issuance | STOCKHOLM/Arlanda
9 HR, https://tafplanner.smhi.se/app.php/production-program |
| 4. Type of landing forecast
Interval of issuance | Not issued |
| 5. Briefing/consultation provided | FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc |
| 6. Flight documentation
Language(s) used | TAF, METAR, SIGMET, Upper air winds
Swedish/English |
| 7. Charts and other information available for
briefing or consultation | SWC, WC, Nordic SIGWX Chart, Low level forecast |
| 8. Supplementary equipment available for
providing information | - |
| 9. ATS units provided with information | JÖNKÖPING TWR |
| 10. Additional information (limitation of service,
etc.) | Flight planning room available. |

ESGJ 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	True BRG and MAG BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APCH RWY
1	2	3	4	5	6
01	018.07° GEO 013° MAG	2203 x 45	PCN 55 F/B/X/T ASPH	574453.48N 0140346.76E GUND 108.0 ft	THR 734.3 ft TDZ 739.0 ft
19	198.08° GEO 193° MAG	2203 x 45	PCN 55 F/B/X/T ASPH	574601.19N 0140428.09E GUND 107.8 ft	THR 739.1 ft TDZ 741.3 ft
11	113.91° GEO 109° MAG	525 x 25	PCN - GRASS	574513.16N 0140405.11E GUND 108 ft	THR 737 ft
29	293.91° GEO 289° MAG	525 x 25	PCN - GRASS	574506.29N 0140434.11E GUND 108 ft	THR 738 ft

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	OFZ	Remarks
7	8	9	10	11	12
01 See ESGJ AOC	-	450 x 180	2380 x 280	-	-
19 See ESGJ AOC	-	190 x 150	2380 x 280	-	-
11	-	-	585 x 60	-	-
29	-	-	585 x 60	-	-

ESGJ 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
01	2203	2653	2203	2203	Intermediate distances, see ESGJ AOC
19	2203	2393	2203	2203	-
11	525	525	525	525	-
29	525	525	525	525	-

DECLARED DISTANCES TAKE-OFF INTERSECTIONS

RWY	INTERSECTION	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1		2	3	4	5	6
01	TWY A	1640	2090	1640	-	-

ESGJ 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type, LEN INTST	THR LGT Colour WBAR	VASIS (MEHT)	TDZ LGT LEN	RWY Centre Line LGT LEN, Spacing Colour INTST	RWY Edge LGT LEN, Spacing Colour INTST	RWY End LGT Colour WBAR	SWY LGT LEN, Colour
1	2	3	4	5	6	7	8	9
01	Calvert CAT I 900 m LIH	Green	PAPI Left/3.00° (55.8 ft)	-	-	2203/50 m White Caution zone 600 m yellow LIH	Red	-
19	Calvert CAT I 900 m LIH	Green	PAPI Left/3.00° (59.7 ft)	-	-	2203/50 m White Caution zone 600 m yellow LIH	Red	-
10 Remarks: -								

ESGJ 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

- ABN/IBN location, characteristics and hours of operation -
- LDI location and LGT Windsock 780 m past THR 01 right side, lighted. Windsocks at RWY ends
Anemometer location and LGT 390 m past THR 01 right side, lighted
540 m past THR 19 left side, lighted
- TWY edge and centre line lighting Edge: TWY A, B
CL: -
- Secondary power supply/switch-over time Available/15 sec, during LVP less than 1 sec
- Remarks -

ESGJ 2.16 HELICOPTER LANDING AREA

RWY 01/19 and 11/29 to be used

ESGJ 2.17 ATS AIRSPACE

- Designation and lateral limits JÖNKÖPING CTR 575647N 0140456E - 575459N 0141548E -
575107N 0141718E - 574025N 0141020E -
573434N 0140322E - 573621N 0135304E -
574156N 0135209E - 575146N 0135801E -
575647N 0140456E
- Vertical limits JÖNKÖPING CTR 2200 ft AMSL
GND
- Airspace classification C
- ATS unit call sign JÖNKÖPING TOWER
Language(s) Swedish/English
- Transition altitude 5000 ft AMSL
- Remarks CTR established during hours of TWR.

ESGJ 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Channel/Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	JÖNKÖPING TOWER	118.255	HO	Primary channel VDF.
		121.500	HO	-

ESGJ 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid CAT of ILS/MLS (for VOR/ILS/MLS give VAR)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
LOC 01 ILS CAT I (5° E 2020)	SGJ	111.50 MHz	H24 *	574607.3N 0140431.8E		199 m beyond THR 19 ILS Class I/E/2
GP		332.90 MHz	H24 *	574504.4N 0140346.7E		Angle 3.0° RDH 56.0 ft 320 m past THR 01 left side
L 01	OJ	403 kHz	H24 *	574147.0N 0140152.2E		Range 25 NM
LOC 19 ILS CAT I (5° E 2020)	SJ	109.90 MHz	H24 *	574442.8N 0140340.2E		349 m beyond THR 01 ILS Class I/E/2
GP		333.80 MHz	H24 *	574552.6N 0140414.8E		Angle 3.0° RDH 50.9 ft 322 m past THR 19 right side
OM				574937.6N 0140644.4E		-
MM				574633.3N 0140447.6E		-
L 19	OA	338 kHz	H24 *	574937.4N 0140644.4E		Range 25 NM
DVOR/DME (5° E 2020)	JON	115.80 MHz	H24 *	574537.6N 0140355.5E	782 ft	DME channel 105X
DME	SGJ	111.50 MHz	H24 *	574504.4N 0140346.4E	762 ft	319 m past THR 01 DME channel 52X

* Monitoring of signal in space limited to ATS HR of OPS

ESGJ 2.20 LOKALA TRAFIKFÖRESKRIFTER

1. Utanför ATS öppethållning ska flygning i trafikvarvet i samband med upprepade start- och landningsövningar RWY 01/19 och RWY 11/29 utföras väster och söder om respektive bana.

LOCAL TRAFFIC REGULATIONS

1. Outside ATS hours of operation, flights in the traffic circuit including repeated take-off and landing exercises RWY 01/19 and RWY 11/29 shall be carried out west and south of respective runway.

2. Övrig flygplatstrafik

För övrig flygplatstrafik, normala in- och utflygningar, start och landning, som inte medför upprepade trafikvarv, ska normala trafikrutiner följas enligt SERA.3225.

Utanför ATS öppethållning är blindsändning obligatoriskt inom CTR.

3. Vid landning enligt VFR utanför ATS öppethållning ska avsikt att landa samt ETA tydligt aviseras på kanal 118.255 och banan ska korsas på minst 1000 ft AGL för att säkerställa fri tillgänglighet samt att uppmärksamma eventuell flygplatspersonal och annan trafik på banan. Är banan inte är tillgänglig i sin fulla längd och bredd ska inte landning genomföras.

4. Vid start utanför ATS öppethållning ska avsikt att starta tydligt aviseras på kanal 118.255. Är banan inte tillgänglig i sin fulla längd och bredd ska inte start genomföras.

5. Fordonstrafik kan förekomma på manöverområdet utanför ATS öppethållning.

2. Other aerodrome traffic

For other aerodrome traffic, normal arrivals and departures, take-off and landing, which not involve flying in the traffic circuit or repeated take-offs and landings, normal traffic procedures must be followed in accordance with SERA.3225.

Outside ATS hours of operations, blind transmission is mandatory within CTR.

3. For VFR landing outside ATS hours of operation the intention to land and ETA shall be clearly declared on channel 118.255 followed by crossing the runway at least 1000 ft AGL in order to verify runway availability and alerting any AD personnel and other traffic on the runway. If the runway is not available in its full length and width, the landing shall not be carried out.

4. For take-off outside ATS hours of operation the intention to take-off shall clearly be declared on channel 118.255. If the runway is not available in its full length and width, the take-off shall not be carried out.

5. Vehicle traffic may occur in the manoeuvring area outside ATS opening hours.

ESGJ 2.21 MINSKNING AV BULLERSTÖRNING

1. Flygplatsföreskrifter

Flygning som inte följer SID
För propellerdrivet flygplan med MTOM överstigande 5700 kg samt för samtliga jetflygplan gäller;
a) högersväng efter start RWY 01 får inte påbörjas före passage av L OA eller
b) vänstersväng efter start RWY 19 får inte påbörjas före passage av L OJ.

Då förhållandena så medger bör reversering utöver «Idle Reverse» eller motsvarande ej användas under tiden 2100-0600 (2000-0500).

APU skall inte användas vid parkering vid andra tillfällen än då så krävs för motorstart eller för reglering av kabintemperatur. Start av APU måste alltid meddelas till ramhandlingpersonal.

2. Skol och övningsflygning

Skolflyg med helikopter är inte tillåtet.

Upprepade inflygningar och/eller start och landningar är ej tillåtet under tiden 2100-0600 (2000-0500).

3. Över tätbebyggt område

Över de centrala delarna av Jönköping och Huskvarna bör luftfartyg inte framföras på lägre höjd än 2000 ft AMSL utom då så är nödvändigt i samband med start och landning.

Angivna flygvägar för ankommande och avgående trafik har upprättats även för att minska bullerstörningar. Luftfartyg skall noggrant följa i klareringen angiven flygväg samt i övrigt framföras så att onödiga bullerstörningar inte förorsakas.

NOISE ABATEMENT PROCEDURES

1. Aerodrome regulations

Aircraft not following SID
For propeller driven aircraft with MTOM exceeding 5700 kg and for all jet aircraft the following applies;
a) after take-off RWY 01 right hand turn must not be initiated until passing L OA or
b) after take-off RWY 19 left hand turn must not be initiated until passing L OJ.

When conditions permit more than «Idle Reverse» or equivalent shall not be used between 2100-0600 (2000-0500).

APU shall not be used on parking unless required for engine start or adjustment of cabin heat. Start of APU must always be reported to ramp handling staff.

2. School and training flights

Helicopter school flights are not permitted.

Repeated approaches and/or take-off and landings are not permitted between 2100-0600 (2000-0500).

3. Over built up areas

Over the central parts of Jönköping and Huskvarna aircraft should not be operated below 2000 ft AMSL except when necessary for take-off or landing.

The routes for inbound and outbound traffic have been established also for noise abatement purposes. Aircraft shall strictly adhere to assigned route and be operated in such a manner that unnecessary noise disturbances are not caused

ESGJ 2.22 FLYGPROCEDURER

FLIGHT PROCEDURES

1. Ankommande IFR-trafik inom Jönköping TMA/CTR

Flygvägar är upprättade enligt sid ESGJ 4-9 till ESGJ 4-16.

Väntlägen (Ref ENR 1.3 mom 9)
Väntlägen är upprättade enligt sid ESGJ 4-1.

Visuellinflygning
Luftfartyg skall bibehålla 2500 ft till final.

2. Avgående IFR-trafik inom Jönköping TMA/CTR

Flygvägar
Flygvägar är upprättade enligt sid ESGJ 4-5 till ESGJ 4-16.

3. Startprocedurer, omnidirectional

1. Inbound IFR traffic within Jönköping TMA/CTR.

Routes established in accordance with pages ESGJ 4-9 through ESGJ 4-16.

Holdings (Ref ENR 1.3 para 9)
Holding patterns are established in accordance with page ESGJ 4-1.

Visual approach
Aircraft shall maintain 2500 ft until on final approach.

2. Outbound IFR traffic within Jönköping TMA/CTR.

Routes
Established in accordance with pages ESGJ 4-5 through ESGJ 4-16.

3. Omnidirectional departure procedures

RWY	Procedure	Significant obstacle		
		Obstacle	Elevation (ft)	Direction (GEO)/Dist (m) from THR
01	Climb straight ahead to MNM turning ALT 1200 ft AMSL. Continue climb to appropriate MSA.	Tree (CIO)	821	023°/3232
19	Climb straight ahead to MNM turning ALT 1300 ft AMSL. Continue climb to appropriate MSA.	Tree (CIO) Terrain	854 906	205°/3548 195°/6730

4. Avbrott i radioförbindelse

Luftfartyg skall följa de föreskrifter som anges i ENR 1.3 mom 10. Under IMC gäller dessutom följande.

4.1 Ankommande klarering mottagen och kvitterad

Normalt är gällande bana gräns för den av ACC meddelade ankommande klareringen. Härvid skall luftfartyget med bibehållande av senast tilldelad och kvitterad flyghöjd följa angiven flygväg till OA L (RWY 19) eller OJ L (RWY 01).

Om gränsen för den av ACC meddelade ankommande klareringen är annan än gällande bana skall luftfartyget med bibehållande av senast tilldelad och kvitterad flyghöjd följa angiven flygväg till denna gräns och därifrån flyga direct till OA L eller OJ L. Har beräknad tidpunkt för inflygning mottagits och kvitterats skall angiven nedgång påbörjas först vid denna tidpunkt.

Efter ankomst över OA L eller OJ L skall erforderlig nedgång utföras i väntläge OSCAR ALFA eller OSCAR JULIET varefter normal instrumentinflygning skall utföras.

4.2 Ankommande klarering ej mottagen och/eller kvitterad

Luftfartyget skall med bibehållande av senast tilldelad och kvitterad flyghöjd flyga via aktuell inpasseringspunkt i TMA direkt till L OA. I väntläge OSCAR ALFA (se ESGJ-5-1 till ESGJ-5-4) skall nedgång utföras till 2800 ft AMSL varefter normal instrumentinflygning till RWY 01 eller RWY 19 skall utföras.

4. Communication failure

Aircraft shall adhere to the procedures stipulated in ENR 1.3 para 10. In addition, in IMC the relevant procedures below shall be applied.

4.1 Inbound clearance received and acknowledged

Clearance limit for the inbound clearance issued by ACC is normally the runway-in-use. When this is the case the aircraft shall, maintaining the level last received and acknowledged, fly the specified route to OA L (RWY 19) or OJ L (RWY 01).

If the clearance limit for the inbound clearance issued by ACC is another than the runway-in-use the aircraft shall, maintaining the level last received and acknowledged, fly the specified route to this limit and then proceed direct to OA L or OJ L. If an expected approach time has been received and acknowledged the descent specified shall not be commenced until that time.

After arrival over OA L or OJ L descent, if required, shall be made in OSCAR ALFA or OSCAR JULIET holding pattern. Thereafter a normal instrument approach shall be carried out.

4.2 No inbound clearance received and/or acknowledged

The aircraft shall maintaining the level last received and acknowledged fly via the relevant TMA entry point direct to L OA. In the holding pattern OSCAR ALFA (see ESGJ-5-1 through ESGJ-5-4) descent to 2800 ft AMSL shall be made. Thereafter a normal instrument approach to RWY 01 or RWY 19 shall be carried out.

5. Lågsiktsprocedurer (LVP) etablerade.

LVP träder i kraft när bansynvidden (RVR) är lägre än 550 m eller när molntäckeshöjden eller vertikalsikten är lägre än 200 ft.

Meddelande om att LVP är i kraft lämnas via ATS.

När LVP tillämpas tillåts endast ett luftfartyg alternativt endast fordon på manöverområdet.

6. VFR-flygning inom Jönköping TMA/CTR.

6.1 Trafikvarvshöjd

Lägsta höjd i trafikvarv är 500 ft GND med undantag väster om RWY 01/19 under perioden 1 MAR-30 SEP då lägsta höjd är 700 ft GND.

6.2 Normala in- och utpasseringspunkter

Se ESGJ 6-1

6.3 Väntlägen

Se ESGJ 6-1

6.4 Avbrott i radioförbindelse

Se ESGJ 6-1

5. Low visibility procedures (LVP) are established.

LVP will be in force when RVR is below 550 m or ceiling or vertical visibility is below 200 ft.

The application of LVP will be announced by ATS.

When LVP is applied only one aircraft or vehicles are allowed in the manoeuvring area.

6. VFR flight within Jönköping TMA/CTR.

6.1 Traffic circuit altitude

Minimum altitude in traffic circuit is 500 ft GND except west of RWY 01/19 during the period 1 MAR-30 SEP when minimum altitude is 700 ft GND.

6.2 Normal entry and exit points

See ESGJ 6-1

6.3 Holdings

See ESGJ 6-1

6.4 Communication failure

See ESGJ 6-1

ESGJ 2.23 ÖVRIG INFORMATION

Reducerad separation tillämpas för luftfartyg med MTOM 2000 kg eller lägre (Kategori 1) enligt AIP AD 1.1 mom 10.

Instrumentinflygningsprocedurerna får inte användas för att landa utanför ATS öppethållning.

ADDITIONAL INFORMATION

Reduced separation is applied to aircraft with MTOM 2000 kg or lower (Category 1) in accordance with AIP AD 1.1 para 10.

Prohibited to use instrument approach procedures for landing outside ATS HR of OPS.

ESGJ 2.24 TILLHÖRANDE KARTOR

AD chart

AOC

Area chart

List of waypoints and significant points

RNAV (GNSS) SID RWY 01

RNAV (GNSS) SID RWY 19

RNAV (GNSS) STAR RWY 01

RNAV (GNSS) STAR RWY 19

SID/STAR RWY 01

SID STAR RWY 19

ATC Surveillance

Minimum ALT chart

IAC ILS or LOC RWY 01

IAC NDB RWY 01

IAC ILS or LOC RWY 19

IAC NDB RWY 19

IAC RNP RWY 01

IAC RNP RWY 19

VAC

RELATED CHARTS

ESGJ 2-1

ESGJ-3-1

ESGJ 4-1

ESGJ 4-3

ESGJ 4-5

ESGJ 4-7

ESGJ 4-9

ESGJ 4-11

ESGJ 4-13

ESGJ 4-15

ESGJ 4-91

ESGJ 5-1

ESGJ 5-2

ESGJ 5-3

ESGJ 5-4

ESGJ 5-5

ESGJ 5-9

ESGJ 6-1