



ARP 670759N 0204844E

AD ELEV 1027 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL
A	15 m	ASPH PCN 22 F/B/X/T	CL HLDG	EDGE	RGL	RGL
B	18 m	ASPH PCN 22 F/B/X/T	CL HLDG	EDGE	RGL	RGL

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
Apron A ASPH PCN 22 F/B/X/T	2	670804.30N 0204845.78E	1002
	3	670803.30N 0204852.25E	997
Apron B ASPH PCN 22 F/B/X/T	1	670807.90N 0204836.08E	1003

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
12	117.94° GEO 109° MAG	670809.63N 0204749.86E GUND 93 ft	PCN 22 F/B/X/T	THR 1027 ft	1714	1714	1714	1714	Barrette CL SALS 150 m LIH	THR Green	PAPI Left/4.00° (49.2 ft)	1714/60 m White Caution zone 600 m yellow LIH	Red
30	297.97° GEO 289° MAG	670743.69N 0204955.50E GUND 93.0 ft	PCN 22 F/B/X/T	THR 971.0 ft TDZ 991 ft	1714	1714	1714	1714	Barrette CL Cat I 900 m LIH	THR Green	PAPI Left/3.00° (55.8 ft)	1714/60 m White Caution zone 600 m yellow LIH	Red

