



ARP 671445N 0230408E		AD ELEV 542 FEET	
TWY NR	WIDTH	Surface Bearing Strength	Day marking
A	22 m	ASPH PCN 20 F/B/X/T	Centerline Edge Stopbar
APRON		INS Coordinates for Aircraft Stands	
Surface Bearing strength		COORD	ELEV
1		671440.66N 0230511.69E	542
2		671440.21N 0230516.26E	541
3		671438.50N 0230511.30E	541

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing Strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
11	118.19° GEO 109° MAG	671458.29N 0230304.47E GUND 80.8 ft	PCN 20 F/B/X/T	THR 540.5 ft TDZ 541.4 ft	2300	2300	2300	2300	Barrette CL 900 m L/L/L/H	THR Green	PAPI Left(3.00° (50.0 ft)	2300/60 m White Caution zone 600 m yellow L/L/L/H	Red
29	298.23° GEO 289° MAG	671423.19N 0230553.46E GUND 81 ft	PCN 20 F/B/X/T	THR 541 ft	2300	2300	2300	2300	SALS 420 m L/L/L/H	THR Green	PAPI Left(3.00° (50.0 ft)	2300/60 m White Caution zone 600 m yellow L/L/L/H	Red

LEGEND See GEN 2.3 Dimensions in m, ELEV in ft