



ARP 653236N 0220725E

AD ELEV 65 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
9 ASPH PCN 55 F/B/X/T	3A	65 32 56.55 N 022 07 17.79 E	41
	3B	65 32 56.58 N 022 07 17.84 E	41
	4A	65 32 55.35 N 022 07 20.48 E	41
	4B	65 32 55.37 N 022 07 20.54 E	41
	5A	65 32 54.06 N 022 07 23.33 E	41
	5B	65 32 54.09 N 022 07 23.39 E	41
	7A	65 32 53.40 N 022 07 26.32 E	41
	7B	65 32 53.58 N 022 07 26.81 E	41
	8	65 32 52.56 N 022 07 28.98 E	41
	20	65 32 57.98 N 022 07 12.97 E	40
	21	65 32 58.43 N 022 07 14.42 E	40
	22A	65 32 57.53 N 022 07 15.67 E	40
22B	65 32 57.68 N 022 07 16.07 E	40	
10 ASPH PCN 18 F/B/X/T	101	65 32 46.42 N 022 07 41.21 E	37
	102	65 32 45.67 N 022 07 39.60 E	37
11 ASPH PCN 34 F/B/X/T	111	65 32 59.87 N 022 07 02.41 E	41
	112	65 32 59.72 N 022 07 06.87 E	41
12A CONC+ASPH PCN 55 R/B/X/T			
12B CONC PCN 55 R/B/X/T			

REMARK:

Long time parking light ACFT Apron 10.

Docking system SAFEGATE stand 3, 4, 5.

De-icing on Apron 12A: Available for ACFT with max wingspan 36 m.

De-icing on Apron 12B and 9: Available for all ACFT. Shall be used by ACFT with wingspan more than 36 m.

Normally taxi into de-icing ramp with nose towards SE.

Nose direction towards NW to be requested in taxi-clearance.

See all guidance signs at the Taxiing Guidance Chart, AD 2-ESPA-2-2