

**AD 2 AERODROMES****ESMK 2.1 AERODROME LOCATION INDICATOR AND NAME****ESMK – KRISTIANSTAD****ESMK 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

- |    |  |   |
|----|--|---|
| 1. | ARP coordinates and site at AD               | 555514N 0140507E RWY 950 m inwards THR 01   |
| 2. | Direction and distance from (city)           | S 7.5 NM from Kristianstad  |
| 3. | Elevation/Reference temperature              | 77 ft/+18.5°C   |
| 4. | Geoid undulation at AD ELEV PSN              | 115 ft  |
| 5. | MAG VAR/Annual change                        | 6° E 2025/+0.2 increasing   |
| 6. | Administration, address, telephone, fax, AFS | Kristianstad Airport AB<br>SE-297 92 Everöd<br>TEL: +46 (0)44 23 88 00<br>FAX: +46 (0)44 23 88 78<br>E-mail: info@kidairport.com<br>AFS: ESMKZTZX<br>Website: www.kidairport.com                        |
| 7. | Types of traffic permitted (IFR/VFR)         | IFR/VFR. Max RWY ref code 4C  |
| 8. | Remarks                                      | PPR request for all IFR shall be made via AD e-mail during AD Administration hours.<br>PN compulsory for VFR outside TWR hours, fill in PN form at <a href="http://www.krfk.se/pn">www.krfk.se/pn</a> . |

**ESMK 2.3 OPERATIONAL HOURS**

- |     |   |   |
|-----|---|---|
| 1.  | AD Administration<br>AD Operating hours | As ATS<br>As ATS  |
| 2.  | Customs and immigration                 | O/R   |
| 3.  | Health and sanitation                   | -   |
| 4.  | AIS Briefing Office                     | FPC H24, +46 (0)8 797 63 40, <a href="http://www.lfv.se/fpc">www.lfv.se/fpc</a> |
| 5.  | ATS Reporting Office (ARO)              | As ATS  |
| 6.  | MET Briefing Office                     | FPC H24, +46 (0)8 797 63 40, <a href="http://www.lfv.se/fpc">www.lfv.se/fpc</a> |
| 7.  | ATS                                     | Ref AIP SUP/NOTAM   |
| 8.  | Fuelling                                | As ATS  |
| 9.  | Handling                                | As ATS  |
| 10. | Security                                | As ATS  |
| 11. | De-icing                                | As ATS  |
| 12. | Remarks                                 | Increased charges outside TWR HR of OPS   |

**ESMK 2.4 HANDLING SERVICES AND FACILITIES**

1.	Cargo-handling facilities	Available by arrangement
2.	Fuel/oil types	Fuel Jet A1, 91 UL Oil -
3.	Fuelling facilities/discharge capacity	Jet A1: 150,000 l, fuel truck 91 UL: 20,000 l
4.	De-icing facilities	Available, Type I and II, mobile unit
5.	Hangar space for visiting ACFT	-
6.	Repair facilities for visiting ACFT	-
7.	Remarks	Fuel supplier Air BP. For 91 UL Air Bp Sterlingcard is necessary. Handling channel 131.805

**ESMK 2.5 PASSENGER FACILITIES**

1.	Hotels	In Kristianstad
2.	Restaurants	In Kristianstad
3.	Transportation	Buses, taxis, rental cars
4.	Medical facilities	In Kristianstad
5.	Bank and Post Office	In Kristianstad
6.	Tourist Office	In Kristianstad
7.	Remarks	-

**ESMK 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1.	AD category for fire fighting	CAT 6, CAT 7 O/R
2.	Rescue equipment	By arrangement, municipal rescue service
3.	Capability for removal of disabled aircraft	By arrangement
4.	Remarks	-

**ESMK 2.7 SEASONAL AVAILABILITY – CLEARING**

1.	Types of clearing equipment	Sweepers, blowers, spreaders, slinger, snowploughs
2.	Clearance priorities	RWY, TWY, Apron
3.	Remarks	-

**ESMK 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1.	Apron surface and strength	Apron ASPH PCN 45 F/B/X/T
2.	Taxiway width, surface and strength	TWY A 23 m ASPH PCN 45 F/B/X/T TWY B 23 m ASPH PCN 45 F/B/X/T TWY C 7.5 m ASPH PCN - TWY D 7.5 m ASPH+GRASS PCN -
3.	ACL, location and elevation	Apron 73 ft
4.	VOR checkpoints	-
5.	INS checkpoints	-
6.	Remarks	-

**ESMK 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1.	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of ACFT stands	Taxi guide lines and signs. Marshalling available
2.	RWY and TWY markings and LGT	RWY 01/19: Designator, THR, TDZ, CL and edges are day marked RTHL, REDL, RENL  TWY A: CL, HLDG day marked. Edge lights, RGL B: CL, HLDG day marked. Edge lights, RGL C: CL, HLDG day marked. RGL D: CL day marked
3.	Stop bars	-
4.	Remarks	-

**ESMK 2.10 AERODROME OBSTACLES**

In Area 2					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT in feet	Markings/ Type, colour	Remarks
a	b	c	d	e	f
ESMK1	Forest	555603.8N 0140523.2E	115 / -	-	-
ESMK2	Shrub	555428.4N 0140501.5E	98 / -	-	-
ESMK3	Forest	555426.9N 0140450.5E	122 / -	-	-
ESMK4	Forest	555423.1N 0140450.1E	132 / -	-	-
ESMK5	Forest	555422.3N 0140457.8E	134 / -	-	-
ESMK6	Forest	555417.1N 0140501.3E	148 / -	-	-
ESMK7	Forest	555415.6N 0140501.2E	160 / -	-	-
ESMK8	Forest	555413.5N 0140458.4E	163 / -	-	-
ESMK9	Forest	555414.2N 0140445.4E	164 / -	-	-
ESMK10	Forest	555046.7N 0140318.1E	535 / -	-	-

In Area 3					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
Not available					

**ESMK 2.11 METEOROLOGICAL INFORMATION PROVIDED**

- Associated MET Office: STOCKHOLM/Arlanda
- Hours of service: H24  
MET Office outside hours
- Office responsible for TAF preparation: STOCKHOLM/Arlanda  
Periods of validity: 9 HR, <https://tafplanner.smhi.se/app.php/production-program>
- Type of landing forecast: Not issued  
Interval of issuance
- Briefing/consultation provided: FPC H24, +46 (0)8 797 63 40, [www.lfv.se/fpc](http://www.lfv.se/fpc)
- Flight documentation: TAF, METAR, SIGMET, Upper air winds  
Language(s) used: Swedish/English
- Charts and other information available for briefing or consultation: SWC, WC, Nordic SIGWX Chart, Low level forecast
- Supplementary equipment available for providing information: -
- ATS units provided with information: KRISTIANSTAD TWR
- Additional information (limitation of service, etc.): Flight planning room available

**ESMK 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

Designations RWY NR	True BRG and MAG BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APCH RWY
1	2	3	4	5	6
01	007.15° GEO 001° MAG	2215 x 45	PCN 45 F/B/X/T ASPH	555442.49N 0140459.97E  GUND 114 ft	THR 77 ft
19	187.15° GEO 181° MAG	2215 x 45	PCN 45 F/B/X/T ASPH	555553.60N 0140515.86E  GUND 114.1 ft	THR 73.8 ft TDZ 73.8 ft
Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	OFZ	Remarks
7	8	9	10	11	12
01 See ESMK AOC	-	250 x 180	2335 x 300	-	-
19 See ESMK AOC	-	350 x 180	2335 x 300	-	-

## ESMK 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
01	2215	2465	2215	2215	-
19	2215	2565	2215	2215	-

## DECLARED DISTANCES TAKE-OFF INTERSECTIONS

RWY Designator	INTERSECTION	TORA (m)	TODA (m)	ASDA (m)	Remarks	
1		2	3	4	5	6
01	TWY A	1050	1300	1050	-	-
01	TWY B	848	1098	848	-	-
01	TWY C	923	1173	923	-	-
19	TWY A	1189	1539	1189	-	-
19	TWY B	1390	1740	1390	-	-
19	TWY C	1300	1650	1300	-	-

## ESMK 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type, LEN INTST	THR LGT Colour WBAR	VASIS (MEHT)	TDZ LGT LEN	RWY Centre Line LGT LEN, Spacing Colour INTST	RWY Edge LGT LEN, Spacing Colour INTST	RWY End LGT Colour WBAR	SWY LGT LEN, Colour
1	2	3	4	5	6	7	8	9
01	-	Green	PAPI Left/3.00° (50.3 ft)	-	-	2215/60 m White Caution zone 600 m yellow LIH	Red	-
19	Calvert CAT I 900 m LIL/LIH	Green	PAPI Left/3.25° (59.0 ft)	-	-	2215/60 m White Caution zone 600 m yellow LIH	Red	-

10 Remarks: RWY 01: TRID FLG W LIH  
RWY 19: EFAS 870-330 m before THR and crossbar 3:c

## ESMK 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

- ABN/IBN location, characteristics and hours of operation -
- LDI location and LGT  
Anemometer location and LGT Lighted windsock S apron, windsocks at THR 01 and THR 19  
870 m N THR 01 and S of ILS GP, lighted
- TWY edge and centre line lighting Edge: TWY A, B  
CL: -
- Secondary power supply/switch-over time Available/15 sec.  
RVR below 800 m and during LVP: Available/1 sec.
- Remarks -

## ESMK 2.16 HELICOPTER LANDING AREA

RWY 01/19 to be used

## ESMK 2.17 ATS AIRSPACE

- |    |                                   |                                     |   |
|----|-----------------------------------|-------------------------------------|---|
| 1. | Designation and lateral limits    | KRISTIANSTAD CTR                    | 560800N 0140150E - 560730N 0141435E -<br>555438N 0141600E - 554350N 0140830E -<br>554418N 0135720E - 555616N 0135536E -<br>560800N 0140150E |
| 2. | Vertical limits                   | KRISTIANSTAD CTR                    | 1700 ft AMSL<br><hr/> GND   |
| 3. | Airspace classification           | C                                   |   |
| 4. | ATS unit call sign<br>Language(s) | KRISTIANSTAD TOWER                  | Swedish/English   |
| 5. | Transition altitude               | 5000 ft AMSL                        |   |
| 6. | Remarks                           | CTR established during hours of TWR |   |

## ESMK 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Channel/ Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	KRISTIANSTAD TOWER	129.355	HO	Primary channel
		121.500	HO	-

## ESMK 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid CAT of ILS/MLS (for VOR/ILS/MLS give VAR)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
L 01	KD	375 kHz	H24 *	555216.5N 0140441.4E		Range 15 NM
LOC 19 ILS CAT I (6° E 2025)	MK	108.50 MHz	H24 *	555429.6N 0140457.1E		402 m beyond THR 01 ILS Class I/E/2
GP		329.90 MHz	H24 *	555544.4N 0140506.5E		Angle 3.25° RDH 51.8 ft 303 m past THR 19 right side
NDB 19	OEM	363 kHz	H24 *	555923.1N 0140603.1E		Range 30 NM
DME	MK	108.50 MHz	H24 *	555544.3N 0140506.7E	88 ft	DME channel 22X

\* Monitoring of signal in space limited to ATS HR of OPS

**ESMK 2.20 LOKALA TRAFIKFÖRESKRIFTER**

## 1. Allmänt

Trafik med luftfartyg med MTOM överstigande 5700 kg skall efter start RWY 19 stiga rakt fram till 1500 ft innan sväng påbörjas. För trafik med MTOM 5700 kg eller mindre gäller högervarv efter start då RWY 19 är i användning.

## 2. Användning av APU

## Ankomst

APU skall stängas av snarast efter parkering.

## Avgång

APU får startas först efter tecken från markpersonalen. Då utomhustemperaturen överstiger 25°C, får APU startas tidigast 10 min före beräknad tid för taxning.

## 3. Parkering utanför ATS öppethållning

Parkering på plattan endast tillåtet under ATS öppethållning. Undantag för SAR, ambulans och polis.

## 4. Fordonstrafik på manöverområdet

Fordonstrafik kan förekomma på manöverområdet utanför ATS öppethållning.

**LOCAL TRAFFIC REGULATIONS**

## 1. General

Aircraft having a MTOM exceeding 5700 kg shall, on take-off RWY 19, climb straight ahead to 1500 ft until turn is initiated. For traffic with MTOM 5700 kg or below, right hand circuit applies after departure when RWY 19 is in use.

## 2. Use of APU

## Arrival

APU shall be shut down soonest after parking.

## Departure

APU shall not be started until OK from ground crew. When the outside temperature exceeds 25°C, APU may be started not earlier than 10 min before estimated time for taxiing.

## 3. Parking outside ATS operational hours

Parking on apron outside ATS operational hours is not allowed. Exceptions for SAR, ambulance and police.

## 4. Vehicle traffic on manoeuvring area

Vehicle traffic may occur on the manoeuvring area outside ATS operational hours.

**ESMK 2.21 MINSKNING AV BULLERSTÖRNING**

Flygning över Everöds samhälle bör undvikas.

**NOISE ABATEMENT PROCEDURES**

Overflying the community of Everöd should be avoided.

**ESMK 2.22 FLYGPROCEDURER**

## 1. Startprocedurer, omnidirectional

RWY	Procedure	Significant obstacle		
		Obstacle	Elevation (ft)	Direction (GEO)/Dist (m) from THR
01	Climb straight ahead to MNM turning ALT 500 ft AMSL. Continue climb to appropriate MSA.	Windmill CIO exist	1027	239°/7740
19	Climb straight ahead with MNM 230 ft/NM (3.8%) to MNM turning ALT 1000 ft AMSL. Continue climb to appropriate MSA.	Antenna CIO exist	853	206°/11530

## 2. Lågsiktsprocedurer (LVP) etablerade

LVP träder i kraft när bansynvidden (RVR) är lägre än 550 m eller när molntäckeshöjden eller vertikalsikten är lägre än 200 ft.

Meddelande om att LVP är i kraft lämnas av ATS.

Lägsta RVR för avgående trafik är 400 m.

Vid RVR mellan 400 m och 300 m, är start endast tillåten om operatören har tillstånd för flygplatstrafik i starkt nedsatt sikt från Transportstyrelsen eller annan behörig myndighet.

När LVP tillämpas skall luftfartyg meddela lämnande av manöverområdet genom att anmäla framme på avsedd parkeringsplats.

## 1. Omnidirectional departure procedures

## 2. Low visibility procedures (LVP) established

LVP will be in force when RVR is below 550 m or ceiling or vertical visibility is below 200 ft.

The application of LVP will be announced by ATS.

Minimum RVR for departing traffic is 400 m.

At RVR between 400 m and 300 m, TKOF is only permitted if the operator has permission for Low Visibility Operations from The Swedish Transport Agency or other competent authority.

When LVP is applied aircraft shall report RWY vacated at stand.

## 3. VFR-flygning inom KRISTIANSTAD CTR

Normala in- och utpasseringspunkter  
Se ESMK 6-1

Väntråge  
Se ESMK 6-1

Avbrott i radioförbindelse  
Se ESMK 6-1

Observera höga vindkraftverk mellan inpasseringspunkt  
Sydväst och flygplatsen.

4. Instrumentinflygningsprocedurerna får inte användas  
utanför ATS öppethållning.

## 3. VFR flight within KRISTIANSTAD CTR

Normal entry and exit points  
See ESMK 6-1

Holding point  
See ESMK 6-1

Communication failure  
See ESMK 6-1

Observe group of high wind turbines between entrypoint  
Southwest and the aerodrome.

4. Instrument approach procedures may not be used  
outside ATS hours of operation.

**ESMK 2.23 ÖVRIG INFORMATION**

Reducerad banseparation tillämpas enligt AD 1.1 mom 10.

**ADDITIONAL INFORMATION**

Reduced runway separation applies in accordance with  
AD 1.1 para 10.

**ESMK 2.24 TILLHÖRANDE KARTOR**

AD chart	
AOC	RWY 01/19
Area Chart	(TMA)
List of waypoints and significant points	
ATC Surveillance	
Minimum ALT chart	
IAC	ILS or LOC RWY 19
IAC	NDB RWY 19
IAC	NDB RWY 01
IAC	RNP RWY 01
IAC	RNP RWY 19
VAC	

**RELATED CHARTS**

ESMK 2-1
ESMK 3-1
ESMK 4-1
ESMK 4-3
ESMK 4-91
ESMK 5-1
ESMK 5-2
ESMK 5-3
ESMK 5-5
ESMK 5-9
ESMK 6-1