



ARP 620252N 0142527E

AD ELEV 1178 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL
A	15 m	PCN 20 F/B/X/T	CL HLDG	EDGE		RGL

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
Apron E ASPH PCN 33 F/B/X/T			
Apron W ASPH PCN 23 F/B/X/T			

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing Strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting					
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	RWY CL	Edge	End
09	087.03° GEO 081° MAG	620250.41N 0142417.28E GUND 109.0 ft	PCN 29 F/B/X/T	THR 1172.7 ft TDZ 1177 ft	1701	1701	1701	1701	Barrette CL Cat I 630 m LIL/LIH	THR Green	PAPI Left/3.00° (50.0 ft)		1701/60 m White Caution zone 575 m yellow LIL/LIH	Red
27	267.06° GEO 261° MAG	620253.24N 0142614.19E GUND 109 ft	PCN 29 F/B/X/T	THR 1177 ft	1701	1701	1701	1701		THR Green	PAPI Left/3.00° (50.0 ft)		1701/60 m White Caution zone 575 m yellow LIL/LIH	Red

REMARK : Caution advised. A row of lights S of RWY may be mistaken for approach light system to RWY 09.  
Note that strip dimensions are non standard for ref code 3C (full strip width is not met for parts of the strip south of runway).

