

ARP 592116N 0175632E

LEGEND See GEN 2.3

AD ELEV 47 FEET

Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL STOPBAR
G1	20 m	PCN 9 F/B/X/T	CL HLDG	EDGE		
R	16 m	PCN 40 F/A/X/T	CL	CL		
S	15 m	PCN 120 F/A/X/T	CL	CL		
T	19 m	PCN 100 F/A/X/T	CL	CL		
Y	19 m	PCN 59 F/A/X/T	CL	CL		
Y1	19 m	PCN 60 F/A/X/T	CL HLDG	CL		RGL STOPBAR
Y2	20 m	PCN 38 F/B/X/T	CL ITHP	CL		
Y3	19 m	PCN 64 F/A/X/T	CL HLDG	CL		RGL STOPBAR
Y4	19 m	PCN 55 F/B/X/T	CL HLDG	CL		RGL STOPBAR
Y5	19 m	PCN 38 F/A/X/T	CL HLDG	CL		RGL STOPBAR
YU	24 m	PCN 71 F/A/X/T	CL ITHP	CL		
YW	24 m	PCN 103 F/A/X/T	CL ITHP	CL		

REMARK: Pilot will receive instructions to change to GND frequency from TWR after landing.

INS Coordinates for Aircraft Stands			
APRON Bearing strength	NR	COORD	ELEV
Apron 1 ASPH PCN 82 F/B/X/T	3	592118.27 N 0175641.31 E	18
	4	592119.31 N 0175638.60 E	17
	5	592120.29 N 0175635.90 E	18
	6	592121.09 N 0175633.30 E	18
Apron 2 ASPH PCN 85 F/B/X/T	7	592123.37 N 0175630.63 E	18
	8	592122.78 N 0175632.72 E	18
	9	592121.82 N 0175635.41 E	17
	10	592120.96 N 0175639.17 E	18
	11	592123.33 N 0175640.65 E	16
	12	592125.10 N 0175639.26 E	15
	13	592126.18 N 0175636.24 E	16
Apron 3 ASPH PCN 80 F/B/X/T	14	592127.26 N 0175633.22 E	18
	15	592128.16 N 0175630.31 E	18
	16	592128.95 N 0175633.26 E	19
	17	592128.02 N 0175635.87 E	18
Apron East ASPH PCN 98 F/A/X/T (W part: PCN 30 F/A/X/T)	18	592126.93 N 0175638.93 E	16
	19	592125.84 N 0175641.98 E	15
Apron 4 ASPH PCN 44 F/B/X/T			
Apron 6 ASPH PCN 14 F/A/X/T			
Apron 7 ASPH PCN 19 F/B/X/T Narrow part connecting to TWY S PCN 12 F/A/X/T			
Apron Remote North ASPH PCN 101 F/A/X/T			

