



ARP 653236N 0220725E

AD ELEV 65 FEET

LEGEND See GEN 2.3

Dimensions in m, ELEV in ft

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
9 ASPH PCN 55 F/B/X/T	3A	65 32 56.55 N 022 07 17.79 E	41
	3B	65 32 56.58 N 022 07 17.84 E	41
	4A	65 32 55.35 N 022 07 20.48 E	41
	4B	65 32 55.37 N 022 07 20.54 E	41
	5A	65 32 54.06 N 022 07 23.33 E	41
	5B	65 32 54.09 N 022 07 23.39 E	41
	6	65 32 53.81 N 022 07 26.35 E	41
	7	65 32 53.38 N 022 07 26.88 E	41
	8	65 32 52.59 N 022 07 29.06 E	41
	20	65 32 57.88 N 022 07 12.19 E	40
10 ASPH PCN 18 F/B/X/T	101	65 32 46.42 N 022 07 41.21 E	37
	102	65 32 45.67 N 022 07 39.60 E	37
11 ASPH PCN 34 F/B/X/T	111	65 32 59.93 N 022 07 02.29 E	41
	112	65 32 59.74 N 022 07 06.82 E	41
12 ASPH PCN 55 F/B/X/T			

REMARK:

Long time parking light ACFT Apron 10.

Docking system SAFEGATE stand 3, 4, 5.

De-icing ramp avbl for ACFT code A-C without restrictions. Code D-E with maximum wingspan 36 m shall also de-ice on the de-icing ramp. ACFT code D-E with wingspan more than 36 m shall de-ice on Apron 8 and 9. Normally taxi into de-icing ramp with nose towards SE.

Nose direction towards NW to be requested in taxi-clearance.

See all guidance signs at the Taxiing Guidance Chart, AD 2-ESPA-2-2