



ARP 583510N 0161447E  
 AD ELEV 32 FEET  
 LEGEND See GEN 2.3  
 Dimensions in m, ELEV in ft

TWY NR	WIDTH	Surface Bearing strength	Day marking		Taxiway lighting	
			Centerline Holding	Edge Centerline	RGL Stopbar	RGL
B	23 m	ASPH PCN 55 F/B/X/T	CL HLDG	EDGE	RGL	RGL
C	15 m	ASPH PCN 55 F/B/X/T	CL HLDG	EDGE	RGL	RGL
D	6 m	ASPH	CL HLDG		RGL	RGL

INS Coordinates for Aircraft Stands			
APRON Surface Bearing strength	NR	COORD	ELEV
Apron ASPH PCN 55 F/B/X/T	1	583502.16N 161355.70E	14
	2	583502.15N 161359.73E	13
	3	583502.12N 161403.15E	12
	4	583502.08N 161406.11E	12
	5	583502.77N 161353.28E	14
	6	583501.79N 161353.48E	15
	7	583500.69N 161354.71E	15

RWY NR	TRUE & MAG BRG	THR PSN Geoid undulation	Bearing strength	THR ELEV and highest ELEV of TDZ of precision APCH RWY	Declared distances				Approach and runway lighting				
					TORA	TODA	ASDA	LDA	APCH	THR TRID TDZ	VASIS (MEHT)	Edge	End
09	090.86° GEO 085° MAG	583510.01N 0161354.08E GUND 91.8 ft	PCN 55 F/B/X/T	THR 13.3 ft TDZ 13.3 ft	2205	2205	2205	2205	Calvert Cat I 540 m LIH	THR Green	PAPI Left/3.00° (55.8 ft)	2205/60 m White Caution zone Yellow LIH	Red
27	270.89° GEO 265° MAG	583508.92N 0161610.53E GUND 91.6 ft	PCN 55 F/B/X/T	THR 32.3 ft TDZ 32.3 ft	2205	2205	2205	2205	Calvert Cat I 900 m LIH	THR Green	PAPI Left/3.00° (55.8 ft)	2205/60 m White Caution zone Yellow LIH	Red
11	115.60° GEO 110° MAG	583524.3N 0161411.4E GUND 92 ft		THR 6 ft	600	600	600	600					
29	295.61° GEO 290° MAG	583516.0N 0161444.8E GUND 92 ft		THR 8 ft	600	600	600	600					

