

AERODROME CHART - ICAO

TWR 118.605 **GÖTEBORG/LANDVETTER**

ARP: 573936N 0121728E
AD ELEV: 507 ft
LEGEND See GEN 2.3

Dimensions in m.
ELEV in feet.
Bearings are magnetic.

RWY/TWY markings/lightings, see ESGG AD 2.9.
Declared Distances, see ESGG AD 2.13
Approach and Runway lighting, see ESGG AD 2.14.

REMARKS:
TWY B, C, D, E, F, Y: Centreline on exit TWY:s within ILS critical/sensitive areas and centreline within 150 m from RWY centreline -alternately green and yellow
MAX wingspan 52 m on TWY D.

TWY	Surface, Bearing Strength	Width
A	ASPH PCN 70 F/B/X/T	23 m
B	ASPH PCN 70 F/B/X/T	23 m
C	ASPH PCN 70 F/B/X/T	23 m
D	ASPH PCN 70 F/B/X/T	23 m
E	ASPH PCN 70 F/B/X/T	23 m
F	ASPH PCN 70 F/B/X/T	23 m
G	ASPH PCN 70 F/B/X/T	23 m
H	ASPH PCN 70 F/B/X/T	23 m
J	ASPH PCN 70 F/B/X/T	23 m
K	ASPH PCN 70 F/B/X/T	23 m
L	ASPH PCN 70 F/B/X/T	23 m
Y	ASPH PCN 70 F/B/X/T	23 m
Z	ASPH PCN 70 F/B/X/T	23 m

Hot Spot
TWY D not to be used for exit RWY 03 unless instructed by TWR

Hot Spot
TWY Z via stand 42/44 NOT to be used from Stand 1, 2 and 3.

Apron	Surface, Bearing Strength
APRON	CONC/ASPH PCN 70 F/B/X/T

THR	BRG	THR POS, GUND	Surface, Bearing Strength	THR ELEV TDZ ELEV	VASIS (MEHT)
03	022°	573858.29N 0121603.75E GUND 116.7 ft	ASPH PCN 81 F/B/X/T	THR 478.3 ft TDZ 493.0 ft	PAPI LEFT /3.00° (59 ft)
21	202°	574034.13N 0121730.95E GUND 116.5 ft	ASPH PCN 81 F/B/X/T	THR 506.4 ft TDZ 506.4 ft	PAPI LEFT /3.00° (56 ft)

