

Prescribed Coding of RNAV STAR for RWY 01L/01R

REMARK:

Aircraft to STOCKHOLM/Arlanda shall not be operated at an airspeed of more than 250 kt IAS below FL100 unless otherwise instructed.

STARs to RWY 01L and RWY 01R are identical. Which RWY to be used will be assigned by ATC in the inbound clearance.

Clearance limit is normally the IAF.

From IAF aircraft will be vectored to final approach.

In case of radio communication failure, see AD 2.22 para 3.

All RNAV STARs are based on GNSS or DME/DME for position update.

ELTOK 8M (ELTOK EIGHT MIKE ARRIVAL)

Path Term	Waypoint Identifier	Fly-over	Course °M(°T)	Dist (NM)	Turn Dir	Altitude (ft AMSL)	Speed Limits (kt)	VPA/RDH (°/ft)	Rec Navaid	Nav Spec
IF	ELTOK	-	-	-	-	-FL110	-	-	-	RNAV 1
TF	SA820	-	102°(109.7°)	6.0	-	-	-	-	-	RNAV 1
TF	SA854	-	152°(159.9°)	6.0	-	-FL080	-	-	-	RNAV 1
TF	OBCIV	-	152°(159.9°)	10.1	-	-	-	-	-	RNAV 1

STAR instruction: ELTOK (FL110 or below) – SA820 – SA854 (FL080 or below) – OBCIV

NILUG 3M (NILUG THREE MIKE ARRIVAL)

Path Term	Waypoint Identifier	Fly-over	Course °M(°T)	Dist (NM)	Turn Dir	Altitude (ft AMSL)	Speed Limits (kt)	VPA/RDH (°/ft)	Rec Navaid	Nav Spec
IF	NILUG	-	-	-	-	-FL150	-	-	-	RNAV 1
TF	SA630	-	018° (026.0°)	18.9	-	-	-	-	-	RNAV 1
TF	TEB	-	355° (003.4°)	26.2	-	-	-	-	-	RNAV 1

STAR instruction: NILUG (FL150 or below) – SA630 – TEB

VACRA 1M (VACRA ONE MIKE ARRIVAL)

Path Term	Waypoint Identifier	Fly-over	Course °M(°T)	Dist (NM)	Turn Dir	Altitude (ft AMSL)	Speed Limits (kt)	VPA/RDH (°/ft)	Rec Navaid	Nav Spec
IF	VACRA	-	-	-	-	-FL150	-	-	-	RNAV 1
TF	SA539	-	174° (182.4°)	15.8	-	-	-	-	-	RNAV 1
TF	SA540	-	174° (182.4°)	16.2	-	-	-	-	-	RNAV 1
TF	TEB	-	191° (198.8°)	13.7	-	-	-	-	-	RNAV 1

STAR instruction: VACRA (FL150 or below) – SA539 – SA540 – TEB

XILAN 5M (XILAN FIVE MIKE ARRIVAL)

Path Term	Waypoint Identifier	Fly-over	Course °M(°T)	Dist (NM)	Turn Dir	Altitude (ft AMSL)	Speed Limits (kt)	VPA/RDH (°/ft)	Rec Navaid	Nav Spec
IF	XILAN	-	-	-	-	-FL150	-	-	-	RNAV 1
TF	SA570	-	246° (254.3°)	12.1	-	-	-	-	-	RNAV 1
TF	TEB	-	246° (254.0°)	15.6	-	-	-	-	-	RNAV 1

STAR instruction: XILAN (FL150 or below) – SA570 – TEB